



Model No.: F16J 4G Wifi Dongle(150Mbps DL / 50Mbps UL)

| | | |
|-------------------|------------------------------------|---|
| Chipset | ASR1803S | |
| Network supported | 4G LTE | FDD B1/3/5(can add FDD B7/8/20 and TDD B38/40/41) |
| | 3G WCDMA: | B1-2100(B5-850/B8-900 can be added) |
| Antenna | 4G main antenna | 1 |
| | 4G diversity antenna | 1 |
| | WiFi antenna | 1 |
| WiFi | support 10 users to share the wifi | |
| | 802.11b/g/n, speed upto 150Mbps | |
| | 2412MHz-2472MHz | |
| Speed | FDD LTE | up to 150Mbps DL / up to 50Mbps UL TDD can be added |
| | HSDPA | up to 42.2Mbps DL |
| | HSUPA | up to 11.5Mbps UL |
| 3GPP | FDD LTE | 3GPP R9 Cat.4(TDD LTE can be added) |
| | HSDPA | 3GPP R7&R8 Cat.24(64QAM) |
| | HSUPA | 3GPP R7&R8 Cat.7(16QAM) |
| Port | USB | 1 |
| | USIM/SIM | 1 |
| Others | Hardware interface | USB interface |
| | Sensitivity | <-105dBm (FER≤0.5%) |
| | Working voltage | 5V DC |
| | Working current | 280~1000mA |
| | Sleep Current | <50mA |
| | Language | English |
| | dimension | 95x25x10mm |
| | weight | 25g |
| | working temperature | -10 to +55℃ |
| | working humidity | 10% to 80% |

| | |
|---------------------|--------------|
| storage temperature | -20 to +70°C |
| storage humidity | 5% to 90% |